



# UNDERCOUNTER DISHWASHER

## ISM-FK50

### STANDARD FEATURES

500 × 500 rack · electronic control

- ✓ Takes the full 500 × 500 mm rack, the size most kitchens already own, so existing baskets carry straight over to the new machine.
- ✓ Four cycles cover the range of work: 90 seconds for glassware, 120 and 180 seconds for plates, and a 9-minute cycle for pans and dried-on soil.
- ✓ Throughput of 40 racks an hour on the short cycle keeps pace with a full dining room; 340 mm wash height clears tall glasses and gastronorm inserts.
- ✓ Electronic control holds the rinse temperature instead of letting it drift with the tank, which is what makes results consistent across a service.
- ✓ Multipower supply technology, stainless-steel wash and rinse arms and a filtered tank. Available three-phase at 400 V or single-phase at 220 V — specify at order.



### PRODUCT SPECIFICATIONS

|                 |                                 |
|-----------------|---------------------------------|
| Dimensions      | 57.2 × 63.3 × 81.4 cm           |
| Rack size       | 500 × 500 mm                    |
| Capacity        | 40 / 30 / 20 / 7 racks per hour |
| Wash cycles     | 90 · 120 · 180 s · 9 min        |
| Max wash height | 340 mm                          |
| Energy source   | 400 V 3N or 220 V single-phase  |